# DPM-1101



#### 10.1" Industrial Touch Monitor with Capacitive or Resistive Touch Screen

### Overview

The DPM-1101 is an 10.1-inch widescreen industrial monitor designed for industrial applications. It features a projected capacitive multi-touch or 5-wire resistive touchscreen, housed within a highly durable metal casing, providing front panel IP65-rated protection from water and dust ingress. It supports three signal interfaces via VGA, DP/HDMI, and DVI. Furthermore, the ultra-thin design of the DPM-1101 enables both VESA 75 mount and panel mount installation, simplifying the installation process in different applications.

#### Features

- 10.1" LED-backlit LCD with capacitive or resistive touch screen
- 1x VGA, 1x DVI, 1x DP/HDMI, 1x USB2.0
- DC-IN 12 to 24V
- Supports VESA 75 mount and panel mount
- IP65 compliant front panel





#### I/O Interfaces



# DPM-1101



### Specifications

| Display                |   |
|------------------------|---|
| Size                   | 10.1 inch   |
| Touch Type             | Projected capacitive multi touch/5-wire resistive touch (optional)        |
| Transmittance          | 87% (capacitive) / 80% (resistive)  |
| Control Interface      | USB   |
| Surface Hardness       | ≥7H   |
|                        | ≥3H   |
| Resolution             | 1920 x 800  |
| Luminance              | 350 nits  |
| Contrast Ratio         | 1000: 1   |
| View Angles            | 80 (left), 80 (right), 80 (up), 80 (down)                                 |
| LED Lifetime           | 25,000 hrs  |
| Color                  | 16.7M   |
| I/O Ports              |   |
| USB                    | 1x USB 2.0  |
| Display                | 1x DP/HDMI (select one), 1x VGA, 1x DVI                                   |
| Power                  |   |
| Button                 | Yes   |
| Remote Power On/Off    | 1x remote switch connector  |
| DC Input               | 12 to 24VDC   |
| Power Connector        | Button  |
| Power Consumption      | 10W   |
| Power Adaptor          | AC-DC, 12V@5A, 60W  |
| Mechanical             |   |
| Dimensions (W x D x H) | 261.5x 174.6 x 29 mm (10.3 x 6.9 x 1.5 inches)                            |
| Weight (N.W.)          | 1.1 kg (4 lbs)  |
| Mounting               | Panel mount, wall mount bracket VESA 75                                   |
| Material               | Aluminum alloy panel, all-metal chassis                                   |
| Environment            |   |
| Operating Temperature  | -10 to 50°C (14 to 122°F)   |
| Storage Temperature    | -20 to 60°C (-4 to 140°F)   |
| Relative Humidity      | 10% to 95% @ 40°C (104°F), non-condensing                                 |
| Vibration              | 5 to 500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis |
| IP Rating              | IP65 compliant (for front panel)  |
| Certification          |   |
| EMC                    | CE FCC  |
| Packing List           |   |
| Packing List           | 1x DPM-1101   |
|                        | 1x AC-DC power adapter  |
|                        | 8x panel mounting buckles   |
|                        | 1x warranty card  |

## DPM-1101



### Dimensions

