

## 8" Industrial Touch Panel PC with Intel® Celeron® Processor

### Overview

The DPC-9080 series is an 8" fanless industrial panel PC based on the Intel® Celeron® J1900 processor. It features a modular design to allow easy CPU board or I/O board upgrades to fulfill customer needs. The DPC-9080 series offers low-power consumption, rich I/O connectivity, and Wi-Fi module expansion. It boasts a sleek design with an IP65 aluminum alloy front panel and a durable metal body, offering superior heat dissipation and high reliability for operation in harsh industrial environments. The DPC-9080 series is an excellent HMI platform for industrial applications and factory automation.

### Features

- 8" LED-backlit LCD with capacitive or resistive touch screen
- Rugged aluminum enclosure and fanless design
- Intel® Celeron® J1900 Processor
- 1x COM, 2x USB, 2x LAN, 1x VGA, 1x HDMI
- Wi-Fi support
- VESA 75 mount and panel mount compatibility
- IP65 compliant front panel



### I/O Interfaces



## Specifications

<b>Display</b>	
Size	8 inch
Touch Type	5-wire resistive touch Projected capacitive multi touch
Transmittance	87% (capacitive) / 80% (resistive)
Control Interface	USB
Surface Hardness	≥3H≥7H
Resolution	1024 x 768
Luminance	400 nits
Contrast Ratio	1000: 1
View Angles	80 (left), 80 (right), 80 (up), 80 (down)
LED Lifetime	30,000 hrs
Color	16.7M
<b>System</b>	
CPU	Intel® Celeron® J1900 (2.0 GHz) Quad-Core processor
Memory	DDR3L 4G 1333/1600MHz (Onboard)
Storage	1x full length Mini PCIe for mSATA SSD
<b>I/O Ports</b>	
USB	1x USB 3.0, 1x USB 2.0
Serial	1x COM (RS-232)
Ethernet	2x GbE LAN
Display	1x HDMI, 1x VGA
Antenna	2x SMA antenna holes
<b>Expansion Slot</b>	
Mini PCIe	1x full length Mini PCIe for Wi-Fi 1x full length Mini PCIe for mSATA
<b>RF Communication</b>	
Wi-Fi	Mini PCIe expansion (optional)
Cellular	Mini PCIe expansion (optional)
Bluetooth	Mini PCIe expansion (optional)
<b>Audio</b>	
Audio	Mic in, line out
Speaker	2Ω5W speaker (optional)
<b>Power</b>	
Button	YES
Remote Power On/Off	1x Remote switch connector
DC Input	12VDC
Power Connector	2-pin phoenix terminal
Power Consumption	15W
Power Adaptor	AC-DC, 12V@5A, 60W
<b>Operating System</b>	
Windows	Windows 7, Windows 10
<b>Mechanical</b>	
Dimensions (W x D x H)	227x 173 x 47 mm (8.9 x 6.8 x 1.8 inches)
Weight (N.W.)	1.7 kg (3.7 lbs)
Mounting	Panel mount, wall mount bracket VESA 75
Material	Aluminum alloy panel, all-metal chassis

Environment	
Operating Temperature	-10 to 50°C (14 to 122°F)
Storage Temperature	-20 to 60°C (-4 to 140°F)
Relative Humidity	10% to 95% @ 40°C (104°F), non-condensing
Vibration	5-500Hz, 0.026 G <sup>2</sup> /Hz, 2.16 Grms, X, Y, Z, 1 hour per axis
Certification	
EMC	CE, FCC
Packing List	
Packing	1x DPC-9080 1x AC-DC power adapter 6x panel mounting buckles 1x warranty card

## Dimensions

